RACE for Dx38

Project:	PX1122M MONITOR DX38 CP3000S V1-0		
Location:			
Company:	Electro-Voice		
Street:	12000 Portland Ave. S		
City:	Burnsville	**Zip-Code:**	55337
State:	MN		
Country:	USA		
Author:	NS		
Date:	08/31/06		

Comment:

1. Limiter settings assume a CP3000S. For use with a P3000, subtract 6 dBu from the limiter threshold on each output.2. "FOH" designates use as front of house or use on a tripod. 3. Channel EQ1 on Outputs 1 and 3 can be adjusted by application or personal preference.

RACE

Program Name: PX1122MM 2W 1-0 | User Memory: 1 | Configuration: Free
Author: NS | Revision: 1-0 | Date:

Master Parameter

	EQ 1	EQ 2	EQ 3	EQ 4	EQ 5	DELAY
Input 2 Source: Right	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Time 2 ms Distance Temperature 20 °C
Input 1	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Time 2 ms Distance Temperature 20 °C
Input 1+2 Source: Left						Time 2 ms Distance Temperature 20 °C

Channel Parameter

	ROUTING	EQ 1	EQ 2	EQ 3	EQ 4	X-OVER	DELAY	DYNAMICS	LEVEL
Output 4 Usage: PX1122M HF	In 2	Type Lo-Shelv Freq 8000 Hz Slope 6 dB Gain -6 dB	Type PEQ Freq 5800 Hz Q 8.0 Gain -7 dB	Type PEQ Freq 4300 Hz Q 7.0 Gain -8 dB	Type PEQ Freq 1880 Hz Q 2.0 Gain -10 dB	Hi-Pass Type Linkw 24 Freq 2000 Hz Lo-Pass Type Butter 24 Freq 16000 Hz Polarity normal	Time 0 us Temperature 20 °C	Compressor Bypass Limiter Thresh 4 dBu Release 50 ms	Level -1 dB Polarity normal Muted No
Output 3 Usage: PX1122M LF	In 2	Type PEQ Freq 90 Hz Q 2.8 Gain 0 dB	Type PEQ Freq 520 Hz Q 4.0 Gain -3 dB	Type PEQ Freq 740 Hz Q 4.0 Gain -6 dB	Type PEQ Freq 1200 Hz Q 4.0 Gain -5 dB	Hi-Pass Type Butter 24 Freq 52 Hz Lo-Pass Type Linkw 24 Freq 2000 Hz Polarity normal	Time 354 us Temperature 20 °C	Compressor Bypass Limiter Thresh 8 dBu Release 80 ms	Level 0 dB Polarity normal Muted No
Output 2 Usage: PX1122M HF	In 1	Type Lo-Shelv Freq 8000 Hz Slope 6 dB Gain -6 dB	Type PEQ Freq 5800 Hz Q 8.0 Gain -7 dB	Type PEQ Freq 4300 Hz Q 7.0 Gain -8 dB	Type PEQ Freq 1880 Hz Q 2.0 Gain -10 dB	Hi-Pass Type Linkw 24 Freq 2000 Hz Lo-Pass Type Butter 24 Freq 16000 Hz Polarity normal	Time 0 us Temperature 20 °C	Compressor Bypass Limiter Thresh 4 dBu Release 50 ms	Level -1 dB Polarity normal Muted No
Output 1 Usage: PX1122M LF	In 1	Type PEQ Freq 90 Hz Q 2.8 Gain 0 dB	Type PEQ Freq 520 Hz Q 4.0 Gain -3 dB	Type PEQ Freq 740 Hz Q 4.0 Gain -6 dB	Type PEQ Freq 1200 Hz Q 4.0 Gain -5 dB	Hi-Pass Type Butter 24 Freq 52 Hz Lo-Pass Type Linkw 24 Freq 2000 Hz Polarity normal	Time 354 us Temperature 20 °C	Compressor Bypass Limiter Thresh 8 dBu Release 80 ms	Level 0 dB Polarity normal Muted No