RACE for Dx38

Project:	PX2122 2-WAY DX38 CP3000S V1-0		
Location:			
Company:	Electro-Voice		
Street:	12000 Portland Ave. S		
City:	Burnsville	**Zip-Code:**	55337
State:	MN		
Country:	USA		
Author:	NS		
Date:	11/07/06		

Comment:

1. Limiter settings assume a CP3000S. For use with a P3000, subtract 6 dBu from the limiter threshold on each output.2. 2-Way settings for (1) PX2122.

RACE

Program Name: PX2122 2W V1-0 | User Memory: 1 | Configuration: Free
Author: NS | Revision: 1-0 | Date: 10/07/06

Master Parameter

	EQ 1	EQ 2	EQ 3	EQ 4	EQ 5	DELAY
Input 2 Source: Right	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Time 2 ms Distance Temperature 20 °C
Input 1	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Type Bypass	Time 2 ms Distance Temperature 20 °C
Input 1+2 Source: Left						Time 2 ms Distance Temperature 20 °C

Channel Parameter

	ROUTING	EQ 1	EQ 2	EQ 3	EQ 4	X-OVER	DELAY	DYNAMICS	LEVEL
Output 4 Usage: PX2122 HF	In 2	Type PEQ Freq 2200 Hz Q 1.0 Gain -10 dB	Type PEQ Freq 2700 Hz Q 4.5 Gain -4 dB	Type PEQ Freq 4700 Hz Q 4.5 Gain -5 dB	Type PEQ Freq 6100 Hz Q 6.0 Gain -6 dB	Hi-Pass Type Linkw 24 Freq 1600 Hz Lo-Pass Type Butter 24 Freq 16000 Hz Polarity normal	Time 0 us Temperature 20 °C	Compressor Bypass Limiter Thresh 4 dBu Release 50 ms	Level 2 dB Polarity normal Muted No
Output 3 Usage: PX2122 LF	In 2	Type PEQ Freq 1300 Hz Q 4.0 Gain 7 dB	Type PEQ Freq 1290 Hz Q 12.0 Gain -5 dB	Type Lo-Shelv Freq 260 Hz Slope 6 dB Gain 6 dB	Type PEQ Freq 660 Hz Q 1.6 Gain -2 dB	Hi-Pass Type Linkw 24 Freq 100 Hz Lo-Pass Type Linkw 24 Freq 1600 Hz Polarity normal	Time 875 us Temperature 20 °C	Compressor Bypass Limiter Thresh 8 dBu Release 80 ms	Level 0 dB Polarity normal Muted No
Output 2 Usage: PX2122 HF	In 1	Type PEQ Freq 2200 Hz Q 1.0 Gain -10 dB	Type PEQ Freq 2700 Hz Q 4.5 Gain -4 dB	Type PEQ Freq 4700 Hz Q 4.5 Gain -5 dB	Type PEQ Freq 6100 Hz Q 6.0 Gain -6 dB	Hi-Pass Type Linkw 24 Freq 1600 Hz Lo-Pass Type Butter 24 Freq 16000 Hz Polarity normal	Time 0 us Temperature 20 °C	Compressor Bypass Limiter Thresh 4 dBu Release 50 ms	Level 2 dB Polarity normal Muted No
Output 1 Usage: PX2122 LF	In 1	Type PEQ Freq 1300 Hz Q 4.0 Gain 7 dB	Type PEQ Freq 1290 Hz Q 12.0 Gain -5 dB	Type Lo-Shelv Freq 260 Hz Slope 6 dB Gain 6 dB	Type PEQ Freq 660 Hz Q 1.6 Gain -2 dB	Hi-Pass Type Linkw 24 Freq 100 Hz Lo-Pass Type Linkw 24 Freq 1600 Hz Polarity normal	Time 875 us Temperature 20 °C	Compressor Bypass Limiter Thresh 8 dBu Release 80 ms	Level 0 dB Polarity normal Muted No